SIEMENS



Approval of Gear Oil

No. A-KP-2009722 acc. request from 30-10-2007

Date of expire: July - 2014

For the gear oil

With a viscosioty range of

Q8 Goya NT

ISO VG 150 - 460

for sale by the company Q8 Kuwait Petrolium R & T B.V.

the compliance with the CLP quality in accordance with DIN 51517-3 is guaranteed by the selling company. The selling company has had performed the following tests according to the Flender

Flender specification for gear oil approvals, Rev. 9 for Helical-, Bevel- and Planetary gear units

with the mentioned oil. The test results were presented to Flender.

- FZG scuffing test 8.3 in accordance with DIN ISO 14635-1
- FE-8-rolling bearing test in acc. with DIN 51819-3
- Compatibility with gear unit internal coatings P22-8050 and Nuvopur Aqua Primer 510.1.1499
- Compatibility with Loctite 128068 liquid sealing compound
- Compatibility with elastomer seal material 72 NBR 902 and 75 FKM 585 static test
- Compatibility with elastomer shaft seals 72 NBR 902 and 75 FKM 585 dynamic test
- Flender oil foaming test
- Grey staining test FVA 54/II

According to the presented test results, the conditions demanded by Flender were satisfied.

We therefore recommend the using of the above mentioned oil for our following gear units

Helical-, Bevel- and Planetary gear units = Table A in our BA 7300

Bocholt, 22-7-2009

A.Friedr. Flender AG

Dryling. Gerhard Gajewski

Quality, Lubricant Management

A.Friedr. Flender AG

huland

Joachim Unland Quality, QMM

A. Friedr. Flender AG, Alfred-Flender-Str. 77, 48395 Bocholt, Phone +49 (0) 2871-92-0, Telefax: +49 (0) 2871-92-2598, www.flender.com