



TURBINENFABRIK J. NADROWSKI GMBH

Lubricating Oil Instructions For Steam Turbines

Proper lubrication of steam turbines largely depends on the quality and the right choice of the oil and is of greatest importance for safe operations. Therefore we recommend the use of a branded turbine oil meeting DIN 51515.

Inhibited turbine oils contain additives which reduce ageing of a turbine oil substantially and offer better rustprotection of all oil-wetted parts. Application is especially economical and ist to be recommended.

All branded turbine oils meeting the above DIN may be used.

	L-TD 46 (Viscosity class ISO VG 46) low ambient temperatures	L-TD 68 (Viscosity class ISO VG 68) normal ambient temperatures
	Aral Kosmol TF 46	Aral Kosmol TF 68
	BP Turbinol S 46	BP Turbinol S 68
	Eterna LTD 46, Eterna LTD EP 46	Eterna LTD 68, Eterna LTD EP 68
	TERESSO 46	TERESSO 68
	Q 8 van Gogh 46	Q 8 van Gogh 68
Mobil	Mobil DTE Oil Medium, Mobil Turbine Oil Medium	Mobil DTE Oil Heavy Medium, Mobil Turbine Oil Heavy Medium
	Shell Turbo Öl T 46	Shell Turbo Öl T 68
	Regalöl R & O 46	Regalöl R & O 68
	Wintershall Wiolan DW 46	Wintershall Wiolan DW 68



Aral Aktiengesellschaft, Bochum
4630 Bochum 1, Wittener Str. 45, Tel. (0234) 315-0



BP oiltech GmbH, Hamburg
Neuhöfer Brückenstr. 127-152, 2102 Hamburg 93, Tel. (040) 75197-0



DEA Mineraloel AG, Hamburg
Überseering 40, 2000 Hamburg 60, Tel. (040) 6375-0



ESSO A.G., Hamburg
Bereich Schmierstoffe
Moorburger Bogen 12, 2000 Hamburg 90, Tele. (040) 77175-1



Kuwait Petroleum (Deutschland) GmbH, Ratingen
Gothaer Str. 18, 4030 Ratingen 1, Tel. (02102) 42026

Mobil

Mobil Oil AG, Hamburg
Steinstr. 5, 2000 Hamburg 1, Tel. (040) 3002-0



Deutsche Shell Aktiengesellschaft, Hamburg
Überseering 35, 2000 Hamburg 60, Tel. (040) 6324-0



TEXACO SERVICES (EUROPE) LTD.
149 Avenue Louise, B- 1050 Brussels/Belgium, Tel. (0032) 2-536-9111



Wintershall AG, Düsseldorf
Vertrieb Mineralölprodukte
Heinrichstr. 73, 4000 Düsseldorf 1, Tel. (0211) 6393-0