

# Damcos® Choice of hydraulic oil

## Hydraulic (mineral) Oils

### List of recommended brands and types for use under non-extreme conditions

Product:	ISO norm:	Type/new indication:
BP	15 22 32 46	Energol HLP 15 (Bartran HV) Energol HLP 22 (Bartran HV) Energol HLP 32 (Bartran HV) Energol HLP 46 (Bartran HV)
CASTROL	15 22 32 46 15 32 46	Hyspin AWS 15 Hyspin AWS 22 Hyspin AWS 32 Hyspin AWS 46 Hyspin AWH-M 15 Hyspin AWH-M 32 Hyspin AWH-M 46
CHEVRON	15 32 46	Mechanism LPS 15 Mechanism LPS 32 Mechanism LPS 46
ELF	15 22 32 46	Visga 15 Visga 22 Visga 32 Visga 46
ESSO/EXXON	15 32 15 32 46 26	Nuto H 15 Nuto H 32 Univis N 15 Univis N 32 Inivis N 46 Univis J 26
MOBIL	15 32 32	DTE 11 M DTE 13 M DTE 24
Q8-KUWAIT PETROLEUM	15 22 32 46	Haydn 15 Haydn 22 Haydn 32 Haydn 46
SHELL	15 37 46 22 32 46	Tellus T 15 Tellus T 32 Tellus T 46 Tellus S 22 Tellus S 32 Tellus S 46
STATOIL	22 46	Hydraway 22 Hydraway 46

# Damcos® Choice of hydraulic oil

SUN OIL	15 22 32 46	Sunvis 815-WR Sunvis 822-WR Sunvis 832-WR Sunvis 846-WR
TEXACO	15 22 32 46	Rando HD 15 Rando HD 22 Rando HD 32 Rando HD 46

## Description

Hydraulic oil provides the hydraulic working processes with energy. In DKMS connection this means energy for valve motions.

The viscosity of the different kinds of oil varies according to the temperature; i.e. high temperature renders a low viscosity and vice versa. Some hydraulic oil types vary more than others. The oil viscosity is an indication of "how sluggish" the oil is. If you change the viscosity, you also change the lubricating characteristics of the oil, especially the adhesion that normally results in the well-known dilemma: to choose suitable hydraulic oil, which means oil with suitable viscosity's and temperature conditions.

In order to decrease operating times and to reduce the power loss in pipes, elbows and various components (solenoid valves etc.), which the oil is to pass on its way to the actuator, the lowest possible viscosity is preferred, whereas the "highest possible" viscosity is preferable in order to protect pumps, solenoid valves and other movable mechanisms.

There are naturally technically and scientifically other conditions than the viscosity (e.g. the vapour pressure) which determine the lubricating characteristics of the oil and minimize the risk of pump cavitation, but based on experience a viscosity within the range

15 cSt. (min.) and 200 cSt.

can comply with the above-mentioned conditions.

The choice of oil is not only a choice of viscosity, but also an evaluation of how cold and warm the oil can get during normal operation under different ambient temperatures (arctical versus tropical conditions).

The choice of oil type is customer's responsibility as the oil is dependent on various conditions, such as pressure, temperature etc.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Damcos® and the Damcos logotype are registered trademarks of Damcos A/S. All rights reserved. The contents of this publication are presented for information purposes only, and while effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, expressed or implied, regarding the products or services described herein or their use or applicability. Standard Terms and Conditions of Sale can be issued by contacting Damcos A/S. We reserve the right to modify or improve the designs and specifications of our products at any time without notice.

### Emerson Process Management

Damcos A/S

Aaderupvej 41

DK-4700 Naestved

Tel +45 5578 7200

Fax +45 5578 7272

[www.emersonProcess.com/marine](http://www.emersonProcess.com/marine)

### For global contacts:

[www.EmersonProcess.com/marine](http://www.EmersonProcess.com/marine)



**EMERSON**  
Process Management